



### **Metallic Murals**

The metallic murals are made from metal, resin and lacquer, these pieces range in thickness from 1 ½" to 2" thick, depending on the design. These murals are recommended for interior walls in commercial and residential environments.

#### **Care and Maintenance**

The metallic murals are sealed with a low-maintenance clear coating which provides excellent resistance to household chemicals, food products, stains and oxidation. Cleaning with a soft cloth or sponge and mild detergent or common non-abrasive household cleaner is sufficient. Use of abrasive cleaners (such as Pine sol, Lysol or bleach) powders, scouring pads, steel wools, etc. will damage the finish. Rinse with clean water and wipe dry with a soft cloth.

#### **Installation**

These murals are intended for interior vertical surface applications only and can be mounted with latex-portland mortar, epoxy adhesives or type 1 organic adhesives, depending upon the application. When grouting, use unsanded commercial latex-portland cement grout suitable for the area of use. For some applications, a bead of colored silicone can be used as alternative to grout.

Remove grout haze. Do not use abrasive cleaners, powders, scouring pads, steelwool, sandpaper, etc. or damage to the finish will result. Thoroughly rinse work with clean water. Use a soft cloth to polish completed work. Do not stack murals on top of each other. Do not lay face down. Do not cut face down.

#### **Caution**

- Do not use on floors.
- Not recommended for exterior use or swimming pools
- Should not be exposed to heat of over 122 degrees F.